

# Vintage

COLORS: DUNE, DRIFT, SNOW, ICE, TAUPE, CEMENTO

**For Vintage "F" & Vintage "S" please consult the respective technical data sheets**

## PRODUCT DESCRIPTION

Ciranova Vintage is a waterborne reaction stain to give a weathered 'vintage' look to wood that contains tannin.

## TECHNICAL DATA

**DENSITY** 1 - 1,15 KG/LT

CONFORM THE EUROPEAN DECO-PAINT DIRECTIVE 2010

## PREPARATION

Sand the wood before with grit 100-120. After sanding the sanding dust must be carefully remove. The best result and effect is obtained on brushed wood.

## USER INSTRUCTIONS

Stir well before use. It is recommended to test the chosen color first before you treat the entire surface. During use, the Vintage must be stirred frequently.

Apply the Vintage generously and evenly with a lye-resistant brush in the direction of the grain. Afterwards equalize with a dry brush.

## DRYING TIME

Drying and reaction time: +/- 8 hours. The drying time is highly dependent on the applied quantity, the environmental temperature, the humidity and ventilation.

## COVERAGE

+/- 15-20 m<sup>2</sup> / liter

## AFTER-TREATMENT

After drying, the upstanding fiber and the excess of pigment must be removed by polishing the surface with with a green pad. Afterwards, the surface should be made dust-free before the Vintage can be finished with an oil from the Ciranova range. To finish with a varnish the Vintage must first be blocked with our 1-coat oil UN1CO.

## PRODUCT INFORMATION

Shelf life: 1 year in closed original packaging.

## SPECIAL REPORTS

Vintage is not frost resistant, therefore do not use or transport below 5 ° c.

The product is corrosive. Don't use materials that can rust. The use of gloves and goggles is necessary. The final color depends on the type of wood, sanding, and the applied amount. Therefore, it is recommended to always test the color on the wood!



5L

1L

Ciranova<sup>®</sup> products are made for the professional user. The instructions specified in the data sheet are formulated after necessary tests were performed and after years of experience. However, they are drawn to our best knowledge and ability. The user must test the application of the product in the for him applicable conditions. Guarantee can not be derived out the text of this technical description.

## PRODUCED BY DEBAL COATINGS NV

Industrieweg 29 – B 8800 Beveren-Roeselare  
tel +32 (0) 51 30 11 40 fax +32 (0) 51 31 26 48  
www.ciranova.be ciranova@ciranova.be